

EVP-10 Color Screen IP Phone

This easy-to-use color screen brand new EVOX IP phone can help you improve work efficiency and ensure high-quality voice communication. Equipped with a 2.4-inch 320*240px color display with an adjustable backlight, it provides users with high-resolution graphics and a colorful experience. The EVP-10 supports 2 SIP accounts, integrated 100M dual Ethernet ports, and is fully compatible with EVOX cloud communication service. In addition, it is easy to set up at 60 and 45 angles on a desk or 15-angle mount on the wall, meeting different application scenarios.

All-new Design, Practical details

EVP-10 provides a new intuitive interface design and a 2.4-inch 320*240px color display with an adjustable backlight, which brings a clear and colorful visual experience to users.

EVOX Voice Quality, Better Calling Experience

Featuring EVOX voice technologies, the EVP-10 delivers excellent sound quality and allows fluent conversations.

High Security, Strong Compatibility

EVP-10 IP phones are well protected by configuration files with AES, SRTP and TLS call encryption, etc. They are also protected by EVOX two-factor authentication process.

Easy Firmware Updates

EVP-10 provides an easy way to check firmware updates. Implement the update by clicking the screen on the IP phone without logging into other platforms or preparing a setup file.

Convenient Speed Dial

EVP-10 IP phones support the Speed dial function from key press 0 to 9. Increase the efficiency of contacting frequent contacts by long pressing the speed dials.

Integrated Whoscall Function

Integrated with the Whoscall service, the caller name provided by Whoscall will be displayed on the color screen when the EVP-10 IP phone receives incoming calls.

Online Management Platforms, Easy Deployment

EVP-10 support simple-to-deploy and easy-to-manage by EVOX web based online admin and can be automatically provisioned, making mass deployment and maintenance extremely easy.



Gogolook | whoscall

- 2.4" 320*240px color display with an adjustable backlight
- 2 x 10/100 Mbps Ethernet port
- 6-Way audio conferencing
- 2 SIP accounts
- EVOX voice
- Support RJ9 headset
- Wall mountable
- Stand with 2 adjustable angles

EVP-10 Specifications

Phone Features

LCD Screen	<ul style="list-style-type: none"> 2.4" 320*240px color display with an adjustable backlight 16-bit depth color
Function Keys	<ul style="list-style-type: none"> 7 Function Keys: message, headset, transfer, mute, redial, hands-free speakerphone, record 4 Soft Keys, 4 navigate Keys, volume+/-
SIP Accounts	<ul style="list-style-type: none"> 2 SIP accounts
Ethernet Ports	<ul style="list-style-type: none"> 2*10/100M (adaptive)
Other Ports	<ul style="list-style-type: none"> 1 x handset port, 1 x RJ9 headset port

Call Features

Basic Function	<ul style="list-style-type: none"> Call hold, mute, DND, redial, auto answer, one-touch speed dial, Hotline, call forward, call waiting, Call transfer (attended/ blind), anonymous call, anonymous call rejection, message waiting indicator (MWI)
Direct IP Call	<ul style="list-style-type: none"> Supported
Phone Book	<ul style="list-style-type: none"> EVOX Internal Phone Book; 2000 records; phonebook search/import/export; XML/LDAP remote phonebook; black list
Call History	<ul style="list-style-type: none"> 60 records; call history: all/missed/dialed/received
6-Way Audio Conferencing	<ul style="list-style-type: none"> Supported

Audio Features

Audio Codec	<ul style="list-style-type: none"> EVOX audio
DTMF	<ul style="list-style-type: none"> In-band, RFC 2833, SIP info

Network

Network Safety	<ul style="list-style-type: none"> SIP Related Features: <ul style="list-style-type: none"> SIP v1 (RFC2543), v2 (RFC3261), NAT Traversal by STUN SIP link mode: proxy mode and peer-to-peer SIP link mode Call server redundancy supported Network Features: <ul style="list-style-type: none"> Static IP and DHCP, IPv4 /IPv6, Dual stack IPv4/IPv6, ARP/RARP, DNS A/DNS SRV/DNS NAPTR, LLDP/CDP/DHCP VLAN; IEEE802.1X; OpenVPN; DSCP, 802.1p QoS Time and Date Synchronization: SNTP, PBX, DHCP Transport: UDP/TCP/TLS; RTP/RTCP/SRTP
----------------	---

Configuration & Maintenance

Auto-provision	<ul style="list-style-type: none"> TR069 (TR104/TR106) FTP/TFTP/HTTP/HTTPS for Auto Provisioning DHCP Option66
Configuration	<ul style="list-style-type: none"> Supports Web configuration and EVOX admin configuration Factory reset, reboot Packet capture, system log

Others

Physical Features

- New Stand, wall mountable
- AC/DC Adapter:
 - AC Input: 100~240V, 50~60Hz
 - DC Output: 5V, 1A
- Power consumption (PSU): 0.87~1.18W
- Relative humidity: 10%~90% (No Condensing)
- Storage temperature: -25~ 65°C
- Operation temperature: 0~45°C
- Dimension (W x D x H): 200mm × 165mm × 47mm
- Made in Vietnam

Package Content

Details

- Packing List:
 - EVOX EVP-10 IP phone, power adapter (optional)
 - Handset with handset cord, Ethernet cable, stand
 - Quick Start Guide
- Size:
 - Qty/CTN: 10 PCS, N.W/CTN: 7.5 kg, G.W/CTN: 9.47 kg
 - Giftbox size: 288mm × 217mm × 60mm
 - Carton size: 448mm × 320mm × 302mm

Certification & Compatibility

Certificated by

