

EVP-20 Color Screen IP Phone

The EVOX EVP-20 IP phone is designed to boost workplace efficiency while delivering reliable, high-quality voice communication. Featuring a 2.4-inch 320×240 color display with adjustable backlight, it provides a clear and intuitive user experience. Supporting up to 3 SIP accounts, the EVP-20 includes dual 10/100 Mbps Ethernet ports with integrated PoE for simple and flexible deployment, while HD voice technology ensures crystal-clear audio for all communications. Fully compatible with the EVOX cloud communication service, it also offers flexible installation with adjustable desk angles (40°/45°) or wall mounting to suit a variety of work environments.

Brand-New Color Display Interface

The EVP-20 features a 2.4-inch 320×240px color LCD display with adjustable backlight, providing a clear and intuitive user experience for easier daily communication and operation.

EVOX Voice Quality for Better Communication

Powered by EVOX voice technology, the EVP-20 delivers stable and crystal-clear audio quality, making every conversation more natural and seamless.

HQ and Branch Communication Integration

Supports browsing HQ and branch contact directories while enabling quick identification and redial of branch calls, improving communication efficiency across multiple locations.

One-Touch Firmware Updates

The EVP-20 supports EVOX OTA online updates, allowing users to easily download and upgrade firmware directly from the IP phone interface for faster and more convenient maintenance.

PoE Power for Simplified Deployment

With integrated PoE support, the EVP-20 can be powered directly through the Ethernet cable, reducing additional power requirements and simplifying installation and cabling.

Integrated Whoscall Caller Identification

Integrated with Whoscall services, the EVP-20 displays caller information directly on the screen, helping users quickly identify unknown and important incoming calls.

Automated Deployment and Login

The EVP-20 supports fast deployment and centralized management through the EVOX online management platform, while automatically completing account login to simplify large-scale installation, maintenance, and device management.



Gogolook | whoscall

- 2.4" 320*240px color display with an adjustable backlight
- 2 x 10/100 Mbps Ethernet ports
- 3-Way audio conferencing
- 3 SIP accounts
- Integrated PoE
- EVOX voice
- Support RJ9 headset
- Wall mountable
- Stand with 2 adjustable angles

EVP-20 Specifications

Phone Features

LCD Screen	<ul style="list-style-type: none"> 2.4" 320*240px color display with an adjustable backlight 16-bit depth color
Function Keys	<ul style="list-style-type: none"> 9 Function Keys: contact, message, transfer, hold, mute, hands-free, redial, headset, conference 4 Soft Keys, 4 navigate Keys, volume+/-
SIP Accounts	<ul style="list-style-type: none"> 3 SIP accounts
Ethernet Ports	<ul style="list-style-type: none"> 2 x 10/100M (adaptive)
Other Ports	<ul style="list-style-type: none"> 1 x handset port, 1 x headset port

Call Features

Basic Function	<ul style="list-style-type: none"> Call Waiting, Call Mute/Unmute, Call Hold/Resume, Speed Dial up to 10 sets, Anonymous Call, Call Forward, Call Transfer, Re-dial, DND, Auto Answer, 3-Way Call Conference, Hot Lines, VMWI
Direct IP Call	<ul style="list-style-type: none"> Supported
Phone Book	<ul style="list-style-type: none"> EVOX Internal Phone Book; 2000 records; phonebook search/import/export EVOX Branch calls
Call History	<ul style="list-style-type: none"> All/missed/dialed/received/transferred Whoscall Information
3-Way Audio Conferencing	<ul style="list-style-type: none"> Supported

Audio Features

Audio Codec	<ul style="list-style-type: none"> EVOX audio, G.711, G.729, G.722 G.167 Acoustic Echo Canceller Packet Loss Compensation
DTMF	<ul style="list-style-type: none"> In-band, RFC 2833, SIP info

Network

Network & Security	<ul style="list-style-type: none"> 10/100 Mbps Ethernet (bridge mode) IP mode: IPv4 / IPv6 / IPv4 & IPv6 IP assignment methods: Static IP / DHCP / PPPoE Supports 802.1X network access authentication Virtual LAN (VLAN) Link Layer Discovery Protocol (LLDP) Quality of Service (QoS) Supports redundant servers HTTPS authentication
--------------------	--

Configuration & Maintenance

Maintenance	<ul style="list-style-type: none"> FTP/TFTP for Network Address Book Web management interface Firmware upgrade Automatic firmware upgrade detection
Configuration	<ul style="list-style-type: none"> Device configuration export/import Phonebook export/import DSS key configuration Factory reset, reboot System log

Others

Physical Features

- New Stand, wall mountable
- AC/DC Adapter:
 - AC Input: 100~240V, 50~60Hz
 - DC Output: 5V, 1A
- Relative humidity: 10%~95%
- Operation temperature: 0~45°C
- Dimension
 - Desk Mount (40°): 178 x 191 x 171 mm
 - Desk Mount (45°): 178 x 180 x 179 mm
 - Wall Mount: 178 x 102 x 216 mm

Package Content

Details

- Packing List:
 - EVOX EVP-20 IP phone, power adapter (optional)
 - Handset with handset cord, Ethernet cable, stand
 - Quick Start Guide
- Package Dimensions: 250mm × 220mm × 55mm
- Carton Dimensions: 460mm × 300mm × 270mm

Certification & Compatibility

Certificated by

